

## GAS FREESTANDING RANGES AND VENTILATION PAIRING GUIDE



### GAS FREESTANDING RANGES

30" REAR CONTROL

30" FRONT CONTROL

KFGG500E

KFGD500E

KFDD500ESS

KSGG700E

KSGB900E

YKSDB900ESS

KSDG950ESS

#### UNDER CABINET HOODS

30" - KVUB400GSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KVUB406GSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - KVUB600DSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KVUB606DSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - KXU2830JSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KXU2836JSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×

#### WALL MOUNT AND ISLAND MOUNT HOODS

30" - KVWB400DSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KVWB406DSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - KVWB600HBS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KVWB606HBS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVIB606DSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×

#### PRO STYLE VENTILATION AND LINERS

30" - KVUC600KSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KVUC606KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVWC906KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
48" - KVWC908KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVWC956KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
48" - KVWC958KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - UVL5430JSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - UVL6036JSS*	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
48" - UVL6048JSS*	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×



**\* Custom hood liners can be used with any of the following blower motors:**

UXB1170KYS (1,170 CFM), UXI1200DYS (1,200 CFM), UXB0585KYS (585 CFM)

**\*\* Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

**ELECTRIC FREESTANDING RANGES AND VENTILATION PAIRING GUIDE**

**ELECTRIC FREESTANDING RANGES**

30" REAR CONTROL | 30" FRONT CONTROL

YKFEG500E | YKFEG510ESS | YKFED500ESS | YKFID500ESS | YKSEG700E | YKSEB900E | KSEG950ESS | KSIB900ESS

**UNDER CABINET HOODS**

30" - KVUB400GSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KVUB406GSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - KVUB600DSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KVUB606DSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - KXU2830JSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KXU2836JSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×

**WALL MOUNT AND ISLAND MOUNT HOODS**

30" - KVWB400DSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KVWB406DSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - KVWB600HBS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KVWB606HBS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVIB606DSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×

**PRO STYLE VENTILATION AND LINERS**

30" - KVUC600KSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - KVUC606KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVWC906KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
48" - KVWC908KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVWC956KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
48" - KVWC958KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - UVL5430JSS	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓	.....	✓
36" - UVL6036JSS*	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
48" - UVL6048JSS*	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×



**\* Custom hood liners can be used with any of the following blower motors:**  
 UXB1170KYS (1,170 CFM), UXI1200DYS (1,200 CFM), UXB0585KYS (585 CFM)

**\*\* Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

**COMMERCIAL STYLE RANGES / RANGETOPS AND VENTILATION PAIRING GUIDE**

**RANGES AND RANGETOPS**

..... 30" COMMERCIAL STYLE RANGES / RANGETOPS ..... 36" COMMERCIAL STYLE RANGES / RANGETOPS ..... 48" COMMERCIAL STYLE RANGES / RANGETOPS .....

**KFDC500J    KFGC500J    KCGC500JSS    KFDC506J    KFGC506J    KCGC506JSS    KFDC558J    KFGC558J    KCGC558JSS**

**UNDER CABINET HOODS**

30" - KVUB400GSS	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVUB406GSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - KVUB600DSS	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVUB606DSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - KXU2830JSS	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KXU2836JSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×

**WALL MOUNT AND ISLAND MOUNT HOODS**

30" - KVWB400DSS	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVWB406DSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - KVWB600HBS	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVWB606HBS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVIB606DSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×

**DOWNDRAFT**

30" - KXD4630YSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KXD4636YSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×

**PRO STYLE VENTILATION AND LINERS**

30" - KVUC600KSS	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVUC606KSS	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
36" - KVWC906KSS	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
48" - KVWC908KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓
36" - KVWC956KSS	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
48" - KVWC958KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓
30" - UVL5430JSS	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - UVL6036JSS*	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
48" - UVL6048JSS*	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓



\* Custom hood liners paired with commercial style ranges and rangetops must be used with blower: UXB1170KYS (1,170 CFM)

**\*\* Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

**GAS COOKTOP AND VENTILATION PAIRING GUIDE**

 **GAS COOKTOPS**

30" GAS COOKTOPS

36" GAS COOKTOPS

**KCGS550ESS    KCGS950ESS    KCGD500GSS    KCGD500GSS    KCGS550ESS    KCGS950ESS    KCGD500GSS**

**UNDER CABINET HOODS**

30" - KVUB400GSS	✓	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
36" - KVUB406GSS	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓
30" - KVUB600DSS	✓	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
36" - KVUB606DSS	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓
30" - KXU2830JSS	✓	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
36" - KXU2836JSS	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓

**WALL MOUNT AND ISLAND MOUNT HOODS**

30" - KVWB400DSS	✓	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
36" - KVWB406DSS	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓
30" - KVWB600HBS	✓	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
36" - KVWB606HBS	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓
36" - KVIB606DSS	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓

**DOWNDRAFT**

30" - KXD4630YSS	✓	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
36" - KXD4636YSS	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓

**PRO STYLE VENTILATION AND LINERS**

30" - KVUC600KSS	✓	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
36" - KVUC606KSS	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓
36" - KVWC906KSS	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓
48" - KVWC908KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
36" - KVWC956KSS	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓
48" - KVWC958KSS	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×
30" - UVL5430JSS*	✓	.....	✓	.....	✓	.....	✓	.....	×	.....	×	.....	×
36" - UVL6036JSS*	×	.....	×	.....	×	.....	×	.....	✓	.....	✓	.....	✓
48" - UVL6048JSS*	×	.....	×	.....	×	.....	×	.....	×	.....	×	.....	×



**\* Custom hood liners can be used with any of the following blower motors:**  
 UXB1170KYS (1,170 CFM), UXI1200DYS (1,200 CFM), UXB0585KYS (585 CFM)

**\*\* Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.

**ELECTRIC COOKTOP AND VENTILATION PAIRING GUIDE**

**ELECTRIC COOKTOPS**

	30" ELECTRIC COOKTOPS		30" INDUCTION COOKTOPS		36" ELECTRIC COOKTOPS		36" INDUCTION COOKTOPS	
	KCES550H	KCED600G	KICU500X	KICU509X	KCES556H	KCED606G	KICU569X	

**UNDER CABINET HOODS**

30" - KVUB400GSS	✓	✓	✓	✓	✗	✗	✗
36" - KVUB406GSS	✗	✗	✗	✗	✓	✓	✓
30" - KVUB600DSS	✓	✓	✓	✓	✗	✗	✗
36" - KVUB606DSS	✗	✗	✗	✗	✓	✓	✓
30" - KXU2830JSS	✓	✓	✓	✓	✗	✗	✗
36" - KXU2836JSS	✗	✗	✗	✗	✓	✓	✓

**WALL MOUNT AND ISLAND MOUNT HOODS**

30" - KVWB400DSS	✓	✓	✓	✓	✗	✗	✗
36" - KVWB406DSS	✗	✗	✗	✗	✓	✓	✓
30" - KVWB600HBS	✓	✓	✓	✓	✗	✗	✗
36" - KVWB606HBS	✗	✗	✗	✗	✓	✓	✓
36" - KVIB606DSS	✗	✗	✗	✗	✓	✓	✓

**DOWNDRAFT**

30" - KXD4630YSS	✓	✓	✓	✓	✗	✗	✗
36" - KXD4636YSS	✗	✗	✗	✗	✓	✓	✓

**PRO STYLE VENTILATION AND LINERS**

30" - KVUC600KSS	✓	✓	✓	✓	✗	✗	✗
36" - KVUC606KSS	✗	✗	✗	✗	✓	✓	✓
36" - KVWC906KSS	✗	✗	✗	✗	✓	✓	✓
48" - KVWC908KSS	✗	✗	✗	✗	✗	✗	✗
36" - KVWC956KSS	✗	✗	✗	✗	✓	✓	✓
48" - KVWC958KSS	✗	✗	✗	✗	✗	✗	✗
30" - UVL5430JSS	✓	✓	✓	✓	✗	✗	✗
36" - UVL6036JSS*	✗	✗	✗	✗	✓	✓	✓
48" - UVL6048JSS*	✗	✗	✗	✗	✗	✗	✗



**\* Custom hood liners can be used with any of the following blower motors:**  
 UXB1170KYS (1,170 CFM), UX11200DYS (1,200 CFM), UXB0585KYS (585 CFM)

**\*\* Motor Class CFM rating**

Observe all governing codes and ordinances. Have a qualified technician install the range hood. It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/ rating plate is located inside the range hood on the rear wall of the range hood. Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents. Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance. The canopy range hood is factory set for venting through the roof or through the wall. All openings in ceiling and wall where canopy range hood will be installed must be sealed.

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to installation instructions packaged with product before selecting cabinetry, making cutouts or beginning installation.